

Fine Filter MS9-LFM-G-BUM-HF-DA - Festo 564044

Item no. FES-564044


Manufacturer Festo

EAN 4052568211264

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	20.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Fibre filter
Dichtmaterial	NBR
Filterfeinheit [µm]	1
HS-Code	84213925
Kondensatablass	manual rotary
Material	Aluminium
Medium	Compressed air
Mounting position	vertical ± 5°
Operating conditions	ISO 8573-1
Series	MS9
Temperature (max.)	60
Weight	3.8 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

Model series	MS
size	9
Construction set up	Fibre filter
Filter porosity [µm]	1,00
Condensate drain	Manually rotating
Operating pressure [bar]	0 to 20
Operating medium	Compressed air to ISO 8573-1:2010 [6:8:4]
Air purity class at the output	Compressed air to ISO 8573-1:2010 [5:7:3]
Max. normal flow for air purity class [l/min]	10.000
Min. normal flow for air unit class [l/min]	500

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Filter effective degree [%]	99,9900
Max. condensate amount [ml]	225
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Bearing temperature [°C]	-10 to 60
Residual oil content [mg/m³]	0,50
Fastening type	pipe installation With Accessories Selectively:
installation position	vertical ± 5°
Pneumatic connection 1	Battery module
Pneumatic connection 2	Battery module
Housing material	Aluminium die casting
Cover material	PA
Filter material	Borosilicate fibre
Clamps material	Aluminium wrought alloy
Window material	PA
Seals material	NBR
Product weight [g]	2.500
Differential pressure indicator	Visual display