

Lubricator MS9-LOE-G-U - Festo

564144

Item no. FES-564144

Manufacturer Festo

EAN 4052568211646

Festo air-preparation unit for clean, regulated compressed air that protects downstream components.

TECHNICAL DATA

Betriebsdruck max [bar]	16.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Design	Proportional standard oil mist lubricator
Dichtmaterial	NBR
HS-Code	84248970
Material	Aluminium
Medium	Air
Mounting position	vertical $\pm 5^\circ$
Series	MS9
Temperature (max.)	60
Weight	1.9 kg



STANDARDS & COMPLIANCE

DIN ISO 8573-1

DESCRIPTION

Festo air-preparation unit for clean, regulated compressed air that protects downstream components. The key technical data of this genuine Festo article are listed below.

size	9
Model series	MS
installation position	vertical $\pm 5^\circ$
Construction set up	Proportional standard oil mist lubricator
Max. oil filling volume [cm ³]	490
Clamp protection	Integrated as metal bowl
Operating pressure [bar]	1 to 16
Minimum flow for oiler function [l/min]	100
Operating medium	Air quality class 5:7 acc. to DIN ISO 8573-1
Corrosion resistant class KBK	2 - moderate corrosion stress
Bearing temperature [°C]	-10 to 60

Medium temperature [°C]	-10 to 60
Oil viscosity	ISO VG 32
ambient temperature [°C]	-10 to 60
Product weight [g]	2.000
Fastening type	pipe installation With Accessories
Cover material	PA reinforced
Material information	RoHs compliant
Connection plate material	Aluminium die casting
Seals material	NBR
Housing material	Aluminium die casting
Module connector material	Aluminium die casting
Clamps material	Aluminium wrought alloy
Clamp seal material	NBR
Window material	PA