

Plug NECU-S-M8G4-C2 - Festo

1068198

Item no. FES-1068198

Manufacturer Festo

EAN 4052568061289

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Corrosion resistance class CRC **1 - low corrosion stress**

HS-Code **85366990**

Material **Polyamide (PA)**

Norm **EN 61076-2-104**

Protection rating **IP67**

Series **NECU**

Temperature (max.) **85**

Weight **0.012 kg**



STANDARDS & COMPLIANCE

EN 61076-2-104

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Operating voltage range DC [V]	0 to 30
Operating voltage range AC [V]	0 to 30
Current carrying capacity at 40°C [A]	4,0
Surge voltage strength [kV]	0,8
Protection category	IP67
ambient temperature [°C]	-25 to 85
Material information	RoHs compliant
Degree of contamination	3
Corrosion resistant class KBK	1 - low corrosion stress
Housing material	PA
Plug contacts material	brass, Gold plated
Complies to standard	EN 61076-2-104

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Connection frequency	100
Cable output	straight
Product weight [g]	9,1
Electrical connection 1, design	round
Electrical connection 1, connection type	Plug
Electrical connection 1, connection technology	M8x1 A coded to EN 61076-2-104
Electrical connection 1, number of pins / wires	4
Electrical connection 1, fastening type	Screw lock with SW9
Electrical connection 2, connection technology	Screw clamp
Cable diameter [mm]	3.5 to 5
Conductor - nominal cross-section [mm ²]	0.14 to 0.5
Information about protection category	In mounted condition
Housing colour	 black
Screw lock material	brass, nickel-plated