

Push-In Connector NPQM-D-Q8-S14-P10 - Festo 570458

Item no. FES-570458

Manufacturer Festo

EAN 4052568058463

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	1 - low corrosion stress
Design	Push-pull principle
HS-Code	74122000
Medium	Druckluft
Nennweite DN [mm]	7
Pneumatischer Anschluss	QS-14
Serie	NPQM
Temperature (max.)	70
Weight	0.032 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	7,0
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0,95 to 16
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-20 to 70
Product weight [g]	31,5
Pneumatic connection 1	Plug sleeve QS-14
Pneumatic connection 2	For hose exterior diameter 8 mm

Material information

RoHs compliant

Housing material

Nickel-plated brass

Tube seal, hose seal material

NBR