

Push-In Connector QSM-3H-2 - Festo 133035

Item no. FES-133035

Manufacturer Festo

EAN 4052568029180

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	39174000
Weight	0.0008 kg
Werkstoff	PBT



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Mini
Nominal width [mm]	1,1
Seal type on stud	gasket
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 6
Temperature depending operating pressure [bar]	-0.95 to 14
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]

Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Product weight [g]	0,6
Pneumatic connection 1	Plug sleeve QS-3
Pneumatic connection 2	For hose exterior diameter 2 mm
Sleeve colour	 blue
Material information	RoHs compliant
Housing material	PBT
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels