

## Push-In L-Fitting, Lo QSMLL-M3-2 - Festo 133032

Item no. FES-133032

Manufacturer Festo

EAN 4052568029159

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

### TECHNICAL DATA

|                         |           |
|-------------------------|-----------|
| HS-Code                 | 74122000  |
| Pneumatischer Anschluss | M3        |
| Weight                  | 0.0028 kg |
| Werkstoff               | PBT       |



### STANDARDS & COMPLIANCE

ISO 8573-1:2010

### DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

|                                                     |                                           |
|-----------------------------------------------------|-------------------------------------------|
| size                                                | Mini                                      |
| Nominal width [mm]                                  | 0,8                                       |
| Seal type on stud                                   | gasket                                    |
| installation position                               | arbitrary                                 |
| Packing size                                        | 10                                        |
| Construction set up                                 | Push-pull principle                       |
| Operating pressure complete temperature range [bar] | -0.95 to 6                                |
| Temperature depending operating pressure [bar]      | -0.95 to 14                               |
| Maritime classification                             | see Certificate                           |
| Operating medium                                    | Compressed air to ISO 8573-1:2010 [7:-:-] |

**esd.equipment**

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                                                |                                                                   |
|------------------------------------------------|-------------------------------------------------------------------|
| Information about operating and control medium | Oiled operation possible                                          |
| Corrosion resistant class KBK                  | 1 - low corrosion stress                                          |
| ambient temperature [°C]                       | -10 to 80                                                         |
| Product weight [g]                             | 2,7                                                               |
| Pneumatic connection 1                         | Male thread M3                                                    |
| Pneumatic connection 2                         | For hose exterior diameter 2 mm                                   |
| Sleeve colour                                  | <span class="farbe" style="background-color:#009FE3"></span> blue |
| Material information                           | RoHs compliant                                                    |
| Housing material                               | PBT                                                               |
| Sleeve material                                | POM                                                               |
| Tube seal, hose seal material                  | NBR                                                               |
| Hose clamping segment material                 | High-alloyed stainless steels                                     |
| Nominal tightening torque [Nm]                 | 0,48                                                              |
| Tolerance to nominal tightening torque         | ± 55 %                                                            |