

Cartridge QSPLLKG10-3/16-U - Festo 132928

Item no. FES-132928

Manufacturer Festo

EAN 4052568028640

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	39174000
Weight	0.004 kg
Werkstoff	Polyamid (PA)



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	Mini
Nominal width [mm]	2,6
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure complete temperature range [bar]	-0.95 to 10
Maritime classification	see Certificate
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	1 - low corrosion stress

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

ambient temperature [°C]	-5 to 60
Product weight [g]	3,5
Pneumatic connection 1	QSP...10
Pneumatic connection 2	For hose exterior diameter 3/16"
Sleeve colour	 Grey
Material information	RoHs compliant
Housing material	PA reinforced
Sleeve material	POM
Tube seal, hose seal material	NBR
Hose clamping segment material	High-alloyed stainless steels