

## Cartridge QSPLLKG18-5/16-U - Festo 132952

Item no. FES-132952

Manufacturer Festo

EAN 4052568028848

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

### TECHNICAL DATA

|           |               |
|-----------|---------------|
| HS-Code   | 39174000      |
| Weight    | 0.0087 kg     |
| Werkstoff | Polyamid (PA) |



### STANDARDS & COMPLIANCE

ISO 8573-1:2010

### DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

|                                                     |                                           |
|-----------------------------------------------------|-------------------------------------------|
| size                                                | Standard                                  |
| Nominal width [mm]                                  | 5,2                                       |
| installation position                               | arbitrary                                 |
| Packing size                                        | 10                                        |
| Construction set up                                 | Push-pull principle                       |
| Operating pressure complete temperature range [bar] | -0.95 to 10                               |
| Maritime classification                             | see Certificate                           |
| Operating medium                                    | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Information about operating and control medium      | Oiled operation possible                  |
| Corrosion resistant class KBK                       | 1 - low corrosion stress                  |

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| ambient temperature [°C]       | -5 to 60                                                          |
| Product weight [g]             | 8,1                                                               |
| Pneumatic connection 1         | QSP...18                                                          |
| Pneumatic connection 2         | For hose exterior diameter 5/16"                                  |
| Sleeve colour                  | <span class="farbe" style="background-color:#C6C6C6"></span> Grey |
| Material information           | RoHs compliant                                                    |
| Housing material               | PA reinforced                                                     |
| Sleeve material                | POM                                                               |
| Tube seal, hose seal material  | NBR                                                               |
| Hose clamping segment material | High-alloyed stainless steels                                     |