

Manifold Rail VABM-L1-10AS-M5-4 - Festo 566524

Item no. FES-566524


Manufacturer Festo

EAN 4052568100254

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
HS-Code	84819000
Pneumatic connection	M5
Series	VABM
Weight	0.05 kg



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Pitch dimension [mm]	10,5
Max. number of valve spaces	16
Operating pressure [bar]	-0.9 to 10
Permission	RCM mark c CSA us (OL) c UL us - Recognized (OL)
Corrosion resistant class KBK	2 - moderate corrosion stress
Max. tightening torque Slot rail assembly [Nm]	1,5
Max. tightening torque Valve fastening [Nm]	0,45
Max. tightening torque wall assembly [Nm]	3,0
Product weight [g]	42
Pneumatic connection 1	M5
Pneumatic connection 3	M5
Pneumatic connection 5	M5
Material information	RoHs compliant
Connection strip material	Aluminium wrought alloy