

Sub-Base VABS-S2-2S-G12-R3 - Festo 555640

Item no. FES-555640

Manufacturer Festo

EAN 4052568096250

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84819000
Schutzart	IP65
Weight	0.9 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Build.width [mm]	52
Based on standard	ISO 5599-2
installation position	arbitrary
Control air supply	external
Operating pressure [bar]	-0.9 to 10
Operating voltage range DC [V]	24
Surge voltage strength [kV]	0,8
Current carrying capacity at 40°C [A]	2
Degree of contamination	3
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP65 NEMA 4 In mounted condition
ambient temperature [°C]	-5 to 50
Product weight [g]	815
Fastening type	With throughway bores
Material information	RoHs compliant
Connection plate material	Cast aluminium