

## Solenoid Coil VACC-S18-35-A1-3A - Festo 562909

Item no. FES-562909

Manufacturer Festo

EAN 4052568210540

Festo valve for fast, reliable control of compressed-air direction and flow.

### TECHNICAL DATA

|                                |                                          |
|--------------------------------|------------------------------------------|
| Actuation type                 | Electrical                               |
| Corrosion resistance class CRC | 4 - particularly severe corrosion stress |
| HS-Code                        | 85059029                                 |
| Mounting position              | arbitrary                                |
| Protection rating              | IP65                                     |
| Series                         | VACC                                     |
| Temperature (max.)             | 60                                       |
| Weight                         | 0.42 kg                                  |



### STANDARDS & COMPLIANCE

EN 175301-803

### DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

|                                                |                                                                           |
|------------------------------------------------|---------------------------------------------------------------------------|
| installation position                          | arbitrary                                                                 |
| Power-on time                                  | 100 %                                                                     |
| Coil characteristic value                      | 230 V AC: 50/60 Hz, power 3.5 VA                                          |
| Permitted voltage oscillations                 | -15 % / +10 %                                                             |
| Protection category                            | IP65                                                                      |
| ambient temperature [°C]                       | -20 to 60                                                                 |
| Product weight [g]                             | 580                                                                       |
| Electrical connection                          | Wiring diagram Form A acc. to EN 175301-803<br>Plug acc. to EN 175301-803 |
| Material information                           | LABS containing materials included<br>RoHs compliant                      |
| CE certificate (see declaration of conformity) | to EU low voltage directive                                               |

|                               |                                          |
|-------------------------------|------------------------------------------|
| Switching position display    | no                                       |
| Solenoid material             | PA<br>Steel                              |
| Actuation type                | Electrical                               |
| Insulation material class     | H                                        |
| Corrosion resistant class KBK | 4 - particularly severe corrosion stress |