

Suction Cup VASB-55-1/4-PUR-B - Festo 1396063

Item no. FES-1396063

Manufacturer Festo

EAN 4052568062026

Festo vacuum component for safe gripping, holding and handling in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	-0.950000
Corrosion resistance class CRC	2 - moderate corrosion stress
HS-Code	84799070
Medium	Air
Mounting position	arbitrary
Nennweite DN [mm]	4
Series	VASB
Temperature (max.)	60
Weight	0.04 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo vacuum component for safe gripping, holding and handling in automation. The key technical data of this genuine Festo article are listed below.

Height balance suction cup [mm]	20,0
Nominal width [mm]	4,0
Suction diameter [mm]	55
Suction volumes [cm³]	30,400
Connection position	top
installation position	arbitrary
Suction shape	Round folding bellows1.5 times
Operating pressure [bar]	-0,95
Nominal operating pressure [bar]	-0,7
Operating medium	Atmospheric air based on ISO 8573-1:2010 [7:-:-]
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 60

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Holding force for nominal operating pressure [N]	110,00
Product weight [g]	39
Fastening type	Via vacuum connection
vacuum connection	G1/4
colour	 blue
Shore hardness	60 ± 5
Stud material	Zinc pressure cast
Material information	RoHs compliant
Suction cups material	PUR
Effective suction diameter [mm]	44,7