

Electrical Connection VAVE-L1-1L4-LR - Festo 566729

Item no. FES-566729

Manufacturer Festo

EAN 4052568057695

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	85444290
Schutzart	IP40
Weight	0.035 kg
Werkstoff	Polyamid (PA)



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Reverse polarity protection	for operating voltage
Additional functions	Spark suppression Holding current reduction
Signal condition display	LED
Nominal operating voltage DC [V]	24
Surge voltage strength [kV]	0,8
Degree of contamination	3
Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP40
ambient temperature [°C]	-5 to 60
installation position	arbitrary
Product weight [g]	33,5
Electrical connection	Flex
Protection line connection	Not available
Fastening type	Clip

Housing colour	 black
Material information	RoHs compliant
Housing material	PA
Permission	RCM mark
CE certificate (see declaration of conformity)	to EU EMC directive
Connection cross-section [mm²]	0,14
Cable length [MTR]	5,0