

Electrical Connection VAVE-L1-1S2-LR - Festo 566720

Item no. FES-566720


Manufacturer Festo

EAN 4052568057602

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsspannung	24 V DC
Corrosion resistance class CRC	0 - No corrosion stressing
HS-Code	85366990
Mounting position	arbitrary
Schutzart	IP40
Serie	VAVE
Temperature (max.)	60
Weight	0.0051 kg
Werkstoff	Polyamid (PA)



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Reverse polarity protection	for operating voltage
Additional functions	Spark suppression Holding current reduction
Signal condition display	LED
Nominal operating voltage DC [V]	24
Surge voltage strength [kV]	0,8
Degree of contamination	3
Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP40
ambient temperature [°C]	-5 to 60
installation position	arbitrary
Product weight [g]	1,5
Electrical connection	2 pin socket / container /
Protection line connection	Not available
Fastening type	Clip

Housing colour	 black
Material information	RoHs compliant
Housing material	PA
Permission	RCM mark
CE certificate (see declaration of conformity)	to EU EMC directive