

Electrical Connection VAVE-L1-1VL4-LP - Festo 566725

Item no. FES-566725

Manufacturer Festo

EAN 4052568057657

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsspannung	12 V DC
Corrosion resistance class CRC	0 - No corrosion stressing
HS-Code	85444290
Mounting position	arbitrary
Schutzart	IP40
Serie	VAVE
Temperature (max.)	50
Weight	0.033 kg
Werkstoff	Polyamid (PA)



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Reverse polarity protection	Bipolar
Additional functions	Spark suppression
Signal condition display	LED
Nominal operating voltage DC [V]	12 24
Surge voltage strength [kV]	0,8
Degree of contamination	3
Expanded ambient temperature	-5 - 60 °C
Corrosion resistant class KBK	0 - No corrosion stressing
Protection category	IP40
ambient temperature [°C]	-5 to 50
installation position	arbitrary
Product weight [g]	33,5
Electrical connection	Flex
Protection line connection	Not available

Fastening type	Clip
Housing colour	 black
Material information	RoHs compliant
Housing material	PA
Connection cross-section [mm²]	0,14
Cable length [MTR]	5,0