

Hand Slide Valve VBOH-32-G14 - Festo 1302994

Item no. FES-1302994

Manufacturer Festo

EAN 4052568105372

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	12.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.036 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	3/2 bistable
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Actuation type	Manually
Fastening type	Screwable pipe installation
Normal nominal flow [l/min]	1.675
Nominal width [mm]	8,4
Operating pressure [bar]	-0.95 to 12
ambient temperature [°C]	-10 to 80
Housing material	Aluminium wrought alloy anodized
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Pitch dimension [mm]	31,0

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Sealing principle	Soft
installation position	arbitrary
Construction set up	Sleeve pusher
Control type	Direct
Flow direction	Reversible
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	-10 to 80
actuating force [N]	45
Product weight [g]	35
Stud material	Aluminium wrought alloy anodized
Material information	RoHs compliant
Seals material	NBR