

## Quick Exhaust Valve VBQF-D-G14-E - Festo 548003

Item no. FES-548003

Manufacturer Festo

EAN 4052568093174

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

### TECHNICAL DATA

|                         |           |
|-------------------------|-----------|
| Betriebsdruck max [bar] | 10.000000 |
| HS-Code                 | 84812090  |
| Pneumatischer Anschluss | G1/4      |
| Weight                  | 0.26 kg   |
| Werkstoff               | Aluminium |



### STANDARDS & COMPLIANCE

ISO 8573-1:2010

### DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

|                                             |                                             |
|---------------------------------------------|---------------------------------------------|
| Valve function                              | Quick venting                               |
| Pneumatic connection 1                      | G1/4                                        |
| Pneumatic connection 2                      | G1/4                                        |
| Fastening type                              | Screwable                                   |
| Normal flow Venting 6<0 bar [l/min]         | 2.500                                       |
| Normal nominal flow venting 6-5 bar [l/min] | 960                                         |
| Operating pressure [bar]                    | 0.5 to 10                                   |
| ambient temperature [°C]                    | -20 to 80                                   |
| Housing material                            | Aluminium die casting<br>Zinc pressure cast |
| Operating medium                            | Compressed air to ISO 8573-1:2010 [7:4:4]   |
| Nominal width [mm]                          | 7                                           |

|                                                |                                                           |
|------------------------------------------------|-----------------------------------------------------------|
| installation position                          | arbitrary                                                 |
| Information about operating and control medium | Oiled operation possible (required in further operations) |
| Corrosion resistant class KBK                  | 1 - low corrosion stress                                  |
| Medium temperature [°C]                        | -20 to 80                                                 |
| Product weight [g]                             | 253,0                                                     |
| Material information                           | RoHs compliant                                            |
| Seals material                                 | NBR                                                       |
| Normal nominal flow venting [l/min]            | 1.500                                                     |
| Pneumatic connection 3                         | G1/4                                                      |