

Quick Exhaust Valve VBQF-D-G18-E - Festo 547533

Item no. FES-547533

Manufacturer Festo

EAN 4052568092856

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Corrosion resistance class CRC	1 - low corrosion stress
Dichtmaterial	NBR
Funktion	Schnellentlüftung
HS-Code	84812090
Medium	Druckluft
Mounting position	arbitrary
Nennweite DN [mm]	5
Pneumatischer Anschluss	G1/8
Serie	VBQF
Temperature (max.)	80
Weight	0.105 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Valve function	Quick venting
Pneumatic connection 1	G1/8
Pneumatic connection 2	G1/8
Fastening type	Screwable
Normal flow Venting 6>0 bar [l/min]	1.300
Normal nominal flow venting 6>5 bar [l/min]	350
Operating pressure [bar]	0.5 to 10
ambient temperature [°C]	-20 to 80
Housing material	Aluminium die casting Zinc pressure cast
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Nominal width [mm]	5
installation position	arbitrary
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	1 - low corrosion stress
Medium temperature [°C]	-20 to 80
Product weight [g]	102,5
Material information	RoHs compliant
Seals material	NBR
Normal nominal flow venting [l/min]	850
Pneumatic connection 3	G1/8