

Quick Exhaust Valve VBQF-U-G14-E - Festo 548001

Item no. FES-548001

Manufacturer Festo

EAN 4052568093150

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.23 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Valve function	Quick venting
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Fastening type	Screwable
Normal flow Venting 6<0 bar [l/min]	2.500
Normal nominal flow venting 6-5 bar [l/min]	960
Operating pressure [bar]	0.5 to 10
ambient temperature [°C]	-20 to 80
Housing material	Aluminium die casting Zinc pressure cast
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Nominal width [mm]	7

installation position	arbitrary
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	1 - low corrosion stress
Medium temperature [°C]	-20 to 80
Sound level [dB(A)]	75
Product weight [g]	226,0
Material information	RoHs compliant
Seals material	NBR