

Solenoid Valve VZWD-L-M22C-M-G14-20-V-1P4-40 - Festo 1491842

Item no. FES-1491842

Manufacturer Festo

EAN 4052568106409

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

HS-Code 84818079

Schutzart IP65

Weight 0.42 kg

Werkstoff Messing



STANDARDS & COMPLIANCE

EN 175301-803 ISO 8573-1:2010 EN 12266-1

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Construction set up	Directly controlled poppet valve
Actuation type	Electrical
Sealing principle	Soft
installation position	arbitrary
Fastening type	pipe installation
Fitting connection	G1/4
Electrical connection	Wiring diagram Form A acc. to EN 175301-803 Plug Square shape acc. to EN 175301-803
Nominal width [mm]	2,0
Valve function	2/2 closed monostable
Hand assist actuation	none
Flow direction	Not reversible

medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases mineral oil Neutral liquids Water Other media on request
Nominal pressure fitting	100
pressure difference [bar]	0
Coil characteristic value	24 V DC: 11 W
Insulation material class	H
Permitted voltage oscillations	± 10 %
Power-on time	100 %
Reset mode	Mechanical spring
Control type	Direct
Medium pressure [bar]	0 to 40
Max. viscosity [mm²/s]	22
Medium temperature [°C]	-10 to 80
ambient temperature [°C]	-10 to 35
Leak rate to EN 12266-1	A
Flow Kv [m³/h]	0,13
Normal nominal flow [l/min]	140
Shifting time on [ms]	20
Shifting time off [ms]	18
Material information	LABS containing materials included RoHs compliant
Housing material	Brass cast
Material number housing	CW617N
Seals material	FPM
Product weight [g]	550
Protection category	IP65
Corrosion resistant class KBK	1 - low corrosion stress