

# Solenoid Valve VZWD-L-M22C-M-N18-50-V-3AP4-5# - Festo 1492054

<b>Item no.</b>	FES-1492054	<b>Manufacturer</b>	Festo
<b>Manufacturer no.</b>	VZWD-L-M22C-M-N18-50-V-3AP4-5#	<b>EAN</b>	4052568235093

Festo valve for fast, reliable control of compressed-air direction and flow.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84818073</b>
Schutzart	<b>IP65</b>
Weight	<b>0.5 kg</b>
Werkstoff	<b>Edelstahl</b>



## STANDARDS & COMPLIANCE

EN 175301-803 ISO 8573-1:2010 EN 12266-1

## DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Construction set up	Directly controlled poppet valve
Actuation type	Electrical
Sealing principle	Soft
installation position	arbitrary
Fastening type	pipe installation
Fitting connection	1/8 NPT
Electrical connection	Wiring diagram Form A acc. to EN 175301-803 Plug Square shape acc. to EN 175301-803
Nominal width [mm]	5,0
Valve function	2/2 closed monostable
Hand assist actuation	none
Flow direction	Not reversible

medium	Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases mineral oil Neutral liquids Water Other media on request
Nominal pressure fitting	100
pressure difference [bar]	0
Coil characteristic value	230 V AC: 50/60 Hz, pull-in power 18 VA, holding power 15 VA
Insulation material class	F
Permitted voltage oscillations	± 10 %
Power-on time	100 %
Reset mode	Mechanical spring
Control type	Direct
Medium pressure [bar]	0 to 5
Max. viscosity [mm <sup>2</sup> /s]	22
Medium temperature [°C]	-10 to 80
ambient temperature [°C]	-10 to 35
Leak rate to EN 12266-1	A
Flow Kv [m <sup>3</sup> /h]	0,35
Normal nominal flow [l/min]	375
Shifting time on [ms]	20
Shifting time off [ms]	18
Material information	LABS containing materials included RoHs compliant
Housing material	High-alloyed stainless steels
Material number housing	1.4305
Seals material	FPM
Product weight [g]	500
Protection category	IP65
Corrosion resistant class KBK	3 - severe corrosion stress
CE certificate (see declaration of conformity)	to EU low voltage directive