

Solenoid Valve VZWF-B-L-M22C-N34-275-V-1P4-6 - Festo 1492193

Item no. FES-1492193


Manufacturer Festo

EAN 4052568235963

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Electrical
Corrosion resistance class CRC	1 - low corrosion stress
Design	diaphragm valve, Force controlled
Dichtmaterial	FKM
Durchfluss [l/min]	8020
Funktion	2/2 closed monostable
HS-Code	84818087
Material	Brass
Medium	Compressed air, water
Mounting position	Magnet vertical
Nenndruck PN [bar]	40
Nennweite DN [mm]	27,5
Protection rating	IP65
Series	VZWF
Temperature (max.)	35
Weight	1.4 kg



STANDARDS & COMPLIANCE

EN 175301-803 ISO 8573-1:2010 EN 12266-1

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Construction set up	diaphragm valve Force controlled
Actuation type	Electrical
Sealing principle	Soft
installation position	Magnet vertical
Fastening type	pipe installation
Fitting connection	3/4 NPT
Electrical connection	Wiring diagram Form A acc. to EN 175301-803 Plug Square shape acc. to EN 175301-803
Nominal width [mm]	27,5

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Valve function	2/2 closed monostable
Hand assist actuation	none
Flow direction	Not reversible
medium	Compressed air to ISO 8573-1:2010 [7:-:-] Inert gases mineral oil Neutral liquids Water Other media on request
Nominal pressure fitting	40
pressure difference [bar]	0
Coil characteristic value	24 V DC: 11 W
Permitted voltage oscillations	± 10 %
Medium pressure [bar]	0 to 6
Max. viscosity [mm²/s]	22
Medium temperature [°C]	-10 to 80
ambient temperature [°C]	-10 to 35
Leak rate to EN 12266-1	A
Flow Kv [m³/h]	7,5
Normal nominal flow [l/min]	8.020
Shifting time on [ms]	275
Shifting time off [ms]	290
Material information	LABS containing materials included RoHs compliant
Housing material	Brass cast
Material number housing	CW617N
Seals material	FPM
Screws material	High-alloyed stainless steels
Material number screw	1.4301
Product weight [g]	1.500
Protection category	IP65
Corrosion resistant class KBK	1 - low corrosion stress