

Solenoid Valve VZWF-L-M22C-G114-400-V-1P4-10# - Festo 1492155

Item no. FES-1492155

Manufacturer Festo

EAN 4052568235611

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Actuation type	Electrical
Corrosion resistance class CRC	3 - severe corrosion stress
Design	diaphragm valve, Force controlled
Dichtmaterial	FKM
Durchfluss [l/min]	21370
Funktion	2/2 geschlossen monostabil
HS-Code	84818087
Medium	Druckluft, Wasser
Mounting position	Magnet vertical
Nenndruck PN [bar]	40
Nennweite DN [mm]	40
Schutzart	IP65
Serie	VZWF
Temperature (max.)	35
Weight	4.8 kg
Werkstoff	Edelstahl



STANDARDS & COMPLIANCE

EN 175301-803 ISO 8573-1:2010 EN 12266-1

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Construction set up	diaphragm valve Force controlled
Actuation type	Electrical
Sealing principle	Soft
installation position	Magnet vertical
Fastening type	pipe installation
Fitting connection	G1 1/4
Electrical connection	Wiring diagram Form A acc. to EN 175301-803 Plug Square shape acc. to EN 175301-803

Nominal width [mm]	40,0
Valve function	2/2 closed monostable
Hand assist actuation	none
Flow direction	Not reversible
medium	Compressed air to ISO 8573-1:2010 [7:-:-] Inert gases mineral oil Neutral liquids Water Other media on request
Nominal pressure fitting	40
pressure difference [bar]	0
Coil characteristic value	24 V DC: 30 W
Permitted voltage oscillations	± 10 %
Medium pressure [bar]	0 to 10
Max. viscosity [mm²/s]	22
Medium temperature [°C]	-10 to 80
ambient temperature [°C]	-10 to 35
Leak rate to EN 12266-1	A
Flow Kv [m³/h]	20,0
Normal nominal flow [l/min]	21.370
Shifting time on [ms]	620
Shifting time off [ms]	1.140
Material information	LABS containing materials included RoHs compliant
Housing material	Cast stainless steel
Material number housing	1.4581
Seals material	FPM
Screws material	High-alloyed stainless steels
Material number screw	1.4301
Product weight [g]	4.500
Protection category	IP65
Corrosion resistant class KBK	3 - severe corrosion stress
CE certificate (see declaration of conformity)	to EU pressure vessel directive