

Semi-Rotary Drive DAPS-0960-090-R-F14-MW - Festo 8005009

Item no. FES-8005009

Manufacturer Festo

EAN 4052568256586

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	8.400000
HS-Code	84123900
Pneumatischer Anschluss	G1/4
Weight	24 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

Position drive dimensions	0960
Flange drilling screen	F14
Swivel angle [deg]	92
Shaft connection Depth [mm]	38,5
Standard connection to fitting	ISO 5211
Dampening	No dampening
installation position	arbitrary
Principle of operation	double acting
Construction set up	Joch kinematics
Position detection	without
Closing direction	Right closing
Valve connection corresponds to standard	VDI/VDE 3845 (NAMUR)

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Safety Integrity Level (SIL)	Product can be used in SRP/CS up to SIL 2 Low Demand Product can be used in SRP/CS up to SIL 2 High Demand
Operating pressure [bar]	1 to 8.4
Nominal operating pressure [bar]	5,6
CE certificate (see declaration of conformity)	to EU EX protection directive (ATEX)
ATEX gas category	II 2G
ATEX dust category	II 2D
Ex ignition protection type gas	Ex h IIC T6...T3 Gb X
Ex ignition protection type dust	Ex h IIIC T85°C...T200°C Db X
Ex ambient temperature	-20°C <= Ta <= +60°C
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Rotary torque for nominal operating pressure and 0° pivot angle [Nm]	960,0
Rotary torque for nominal operating pressure and 50° pivot angle [Nm]	480,0
Rotary torque for nominal operating pressure and 90° pivot angle [Nm]	720,0
Air consumption a 6 bar per cycle 0°-90°-0° [LTR]	42,35
Product weight [g]	23.800
Shaft connection	T36
Pneumatic connection	G1/4
Material information	RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	FKM NBR PUR
Housing material	Aluminium wrought alloy
Screws material	High-alloyed steel
Shaft material	High-alloyed steel
Material number shaft	1.4305