

Semi-Rotary Drive DAPS-0480-090-R-F1012-MW - Festo 8005006

Item no.	FES-8005006	Manufacturer	Festo
Manufacturer no.	DAPS-0480-090-R-F1012-MW	EAN	4052568256555

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	8.400000
Condition of article	New
HS-Code	84123900
Pneumatischer Anschluss	G1/4
Weight	13.2 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

Position drive dimensions	0480
Flange drilling screen	F10 F12
Swivel angle [deg]	92
Shaft connection Depth [mm]	29,5
Standard connection to fitting	ISO 5211
Dampening	No dampening
installation position	arbitrary
Principle of operation	double acting
Construction set up	Joch kinematics
Position detection	without

Closing direction	Right closing
Valve connection corresponds to standard	VDI/VDE 3845 (NAMUR)
Safety Integrity Level (SIL)	Product can be used in SRP/CS up to SIL 2 Low Demand Product can be used in SRP/CS up to SIL 2 High Demand
Operating pressure [bar]	1 to 8.4
Nominal operating pressure [bar]	5,6
CE certificate (see declaration of conformity)	to EU EX protection directive (ATEX)
ATEX gas category	II 2G
ATEX dust category	II 2D
Ex ignition protection type gas	Ex h IIC T6...T3 Gb X
Ex ignition protection type dust	Ex h IIIC T85°C...T200°C Db X
Ex ambient temperature	-20°C <= Ta <= +60°C
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Rotary torque for nominal operating pressure and 0° pivot angle [Nm]	480,0
Rotary torque for nominal operating pressure and 50° pivot angle [Nm]	240,0
Rotary torque for nominal operating pressure and 90° pivot angle [Nm]	360,0
Air consumption a 6 bar per cycle 0°-90°-0° [LTR]	22,40
Product weight [g]	13.200
Shaft connection	T27
Pneumatic connection	G1/4
Material information	RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	FKM NBR PUR
Housing material	Aluminium wrought alloy
Screws material	High-alloyed steel
Shaft material	High-alloyed steel
Material number shaft	1.4305