

Clamping Unit DADL-EL-Q11-25 - Festo 1568183

Item no. FES-1568183

Manufacturer Festo

EAN 4052568240356

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84123100
Pneumatischer Anschluss	M5
Weight	0.41 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	25
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 60
Product weight [g]	370
Fastening type	With Throughway bore and centring sleeve
Material information	RoHs compliant
Screws material	Steel zinc plating
Settings range swivel angle [deg]	60 to 200
Construction set up	Piston piston rod
Position detection	For proximity switch
Operating pressure [bar]	5 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]

Information about operating and control medium	Oiled operation possible (required in further operations)
Pneumatic connection	M5
Seals material	NBR TPE-U(PU)
Housing material	aluminium Hard anodised
Housing cover material	aluminium anodized
Bearing material	Plastic
Washer material	aluminium anodized
Principle of operation	single action Pulling
Mounting material	aluminium anodized