

Sub-Base VMPA1-IC-AP-S-1-EX1E - Festo 8005150

Item no. FES-8005150

Manufacturer Festo

EAN 4052568257248

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Corrosion resistance class CRC	0 - No corrosion stressing
HS-Code	84819000
Pneumatic connection	M7
Series	VMPA1
Temperature (max.)	50
Weight	0.135 kg



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Product weight [g]	92,0
Material information	RoHs compliant
Width [mm]	20,2
Length [mm]	107,3
Pitch dimension [mm]	10,5
Operating pressure [bar]	-0.9 to 10
Control pressure [bar]	3 to 8
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-5 to 50
Pneumatic connection 2	M7
Pneumatic connection 4	M7
Connection plate material	Aluminium die casting
Pneumatic connection 1	M7
KC-mark	KC-EMV

CE certificate (see declaration of conformity)	to EU EMC directive to EU EX protection directive (ATEX)
Electrical connection	M8 Plug
Fastening type connection plate	With throughway bores
Pneumatic connection 3	M7
Pneumatic connection 5	M7
Support air control connection 12/14	M5
Exhaust control connection 82/84	M5
ATEX gas category	II 3G
Ex ignition protection type gas	Ex nA IIC T4 X Gc
Ex ambient temperature	-5°C <= Ta <= +50°C