


Sub-Base VMPAL-AP-20-QS3/8"-2-T1 - Festo 561028

Item no.	FES-561028	Manufacturer	Festo
Manufacturer no.	VMPAL-AP-20-QS3/8"-2-T1	EAN	4052568098889

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Article authenticity	Original product
Betriebsdruck max [bar]	10.000000
Condition of article	New
HS-Code	84819000
Weight	0.082 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Width [mm]	21,2
Length [mm]	107,3
Pitch dimension [mm]	21,2
Valve size [mm]	20
Max. number of valve spaces	1
Flow direction	Reversible
Valve island structure	Valve sizes mixable
Operating pressure [bar]	-0.9 to 10
Control pressure [bar]	3 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	3 - severe corrosion stress

ambient temperature [°C]	-5 to 50
Product weight [g]	82,28
Pneumatic connection 2	For hose exterior diameter 3/8"
Pneumatic connection 4	For hose exterior diameter 3/8"
Material information	RoHs compliant
Connection plate material	PA reinforced
Pressure zone separation	Channel 1
Max. number of valve coils	2