

Electrical Connection VAVE-L1-1R8-LR - Festo 573920

Item no. FES-573920

Manufacturer Festo

EAN 4052568059255

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	85366990
Schutzart	IP65
Weight	0.0048 kg
Werkstoff	Polyamid (PA)



DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Reverse polarity protection	Bipolar
Additional functions	Spark suppression Holding current reduction
Signal condition display	LED
Nominal operating voltage DC [V]	24
Surge voltage strength [kV]	0,8
Degree of contamination	3
Corrosion resistant class KBK	2 - moderate corrosion stress
Protection category	IP65
ambient temperature [°C]	-5 to 60
installation position	arbitrary
Product weight [g]	3,2
Electrical connection	M8 / - plug / socket / container / 3-pin / 2-pin
Protection line connection	Not available
Fastening type	on solenoid valve with self-cutting screw

Housing colour	> black
Material information	RoHs compliant
Housing material	PA
Permission	RCM mark
CE certificate (see declaration of conformity)	to EU EMC directive
Max. tightening torque [Nm]	0,27