

Push-In T-Fitting NPQP-T-R14-Q4-FD-P10 - Festo 133072

Item no. FES-133072

Manufacturer Festo

EAN 4052568029555

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	39174000
Pneumatischer Anschluss	R1/4
Weight	0.0064 kg
Werkstoff	Polypropylen (PP)



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	2,0
Packing size	10
Construction set up	Push-pull principle
Temperature depending operating pressure [bar]	-0.95 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	4 - particularly severe corrosion stress
Food compatibility	See expanded material information
ambient temperature [°C]	-20 to 60
Product weight [g]	6,5

Pneumatic connection 1	R1/4
Pneumatic connection 2	For hose exterior diameter 4 mm
Material information	LABS containing materials included RoHs compliant
Housing material	PP
Hose clamping segment material	High-alloyed stainless steels