

Push-In Fitting NPQH-D-G14-S12-P10 - Festo 578366

Item no. FES-578366

Manufacturer Festo

EAN 4052568060695

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	3 - severe corrosion stress
Design	Push-pull principle
HS-Code	74122000
Material	Brass
Medium	Compressed air, water
Mounting position	arbitrary
Nennweite DN [mm]	8,5
Norm	NSF/ANSI 169
Operating conditions	ISO 8573-1
Pneumatic connection	G1/4
Series	NPQH
Temperature (max.)	150
Weight	0.023 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
installation position	arbitrary
Packing size	10
Operating pressure complete temperature range [bar]	-0.95 to 20
Certified awarding point	NSF C0523185
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com
esd.equipment

Page 1/2

Corrosion resistant class KBK	3 - severe corrosion stress
Food compatibility	NSF/ANSI 169 siehe Konformitätserklärung
ambient temperature [°C]	0 to 150
Product weight [g]	22,2
Pneumatic connection 1	Male thread G1/4
Material information	RoHs compliant
Housing material	Nickel-plated brass
Nominal width [mm]	8,50
Seal type on stud	gasket
Construction set up	Push-pull principle
Max. tightening torque [Nm]	15,0
Pneumatic connection 2	Plug sleeve QS-12
Thread sealing material	FPM
Sleeve material	Nickel-plated brass