

Push-In T-Fitting NPQH-T-G14-Q12-P10 - Festo 578398

Item no. FES-578398

Manufacturer Festo

EAN 4052568061012

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

HS-Code	74122000
Pneumatischer Anschluss	G1/4
Weight	0.08 kg
Werkstoff	Messing



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
installation position	arbitrary
Packing size	10
Operating pressure complete temperature range [bar]	-0.95 to 20
Certified awarding point	NSF C0523185
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	3 - severe corrosion stress
Food compatibility	NSF/ANSI 169 siehe Konformitätserklärung

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

ambient temperature [°C]	0 to 150
Product weight [g]	77,4
Pneumatic connection 1	Male thread G1/4
Material information	RoHs compliant
Housing material	Nickel-plated brass
Nominal width [mm]	8,50
Seal type on stud	gasket
Construction set up	Push-pull principle
Max. tightening torque [Nm]	15,0
Pneumatic connection 2	For hose exterior diameter 12 mm
Thread sealing material	FPM
Sleeve material	Nickel-plated brass
Tube seal, hose seal material	FPM
Hose clamping segment material	High-alloyed stainless steels