

Stopper Cylinder DFSP-16-10-F-PA - Festo 576062

Item no. FES-576062

Manufacturer Festo

EAN 4052568224264

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	16.000000
HS-Code	84123100
Hub [mm]	10.000000
Pneumatischer Anschluss	M5
Weight	0.125 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	10
Piston diameter	16 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting Pulling
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Anti-twist lock / guide	Round piston rod
Operating pressure [bar]	2.8 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 80
Impact strength [N]	880
Permitted shear force during switching process [N]	147
Max. cycle frequency [Hz]	5
Fastening type	With throughway bores With female thread With Accessories Selectively:
Pneumatic connection	M5
Material information	RoHs compliant
Flush screw material	High-alloyed stainless steels
Cover material	Aluminium wrought alloy anodized
Seals material	TPE-U(PU)
Piston rod material	High-alloyed stainless steels
Roller material	Zinc plated steel
Cylinder tube material	Aluminium wrought alloy Smooth anodised
Piston rod thread	M3
Piston rod end	Female thread