

Stopper Cylinder DFSP-20-10-PS-PA - Festo 576078

Item no. FES-576078

Manufacturer Festo

EAN 4052568224424

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
Bohrung (mm)	20.000000
HS-Code	84123100
Hub [mm]	10.000000
Pneumatischer Anschluss	M5
Weight	0.21 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	10
Piston diameter	20 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	single action Pulling
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Anti-twist lock / guide	Round piston rod
Operating pressure [bar]	1.6 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 80
Impact strength [N]	1.370
Permitted shear force during switching process [N]	228
Max. cycle frequency [Hz]	5
Fastening type	With throughway bores With female thread With Accessories Selectively:
Pneumatic connection	M5
Material information	RoHs compliant
Flush screw material	Zinc plated steel
Cover material	Aluminium wrought alloy anodized
Seals material	TPE-U(PU)
Piston rod material	High-alloyed stainless steels
Roller material	Zinc plated steel
Cylinder tube material	Aluminium wrought alloy Smooth anodised