

Silencer UC-3/8-20 - Festo 576759

Item no. FES-576759

Manufacturer Festo

EAN 4052568059590

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84879090
Pneumatischer Anschluss	G3/8
Weight	0.011 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

installation position	arbitrary
Packing size	20
Operating pressure [bar]	0 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible
Sound level [dB(A)]	60
ambient temperature [°C]	-10 to 70
Product weight [g]	10,5
Pneumatic connection	G3/8
Dampening insert material	PE
Stud material	PE

Material information

RoHs compliant

Flow against atmosphere [l/min]

5.000

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 2/2