

Fitting NPCK-C-D-G14-K8 - Festo 1691701

Item no. FES-1691701

Manufacturer Festo

EAN 4052568062309

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Corrosion resistance class CRC	4 - particularly severe corrosion stress
HS-Code	73072910
Material	Stainless steel
Medium	Compressed air, water
Mounting position	arbitrary
Nennweite DN [mm]	4,9
Pneumatic connection	G1/4
Series	NPCK
Temperature (max.)	120
Weight	0.032 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4,9
Seal type on stud	gasket
installation position	arbitrary
Packing size	1
Operating pressure complete temperature range [bar]	-0.95 to 12
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible
Corrosion resistant class KBK	4 - particularly severe corrosion stress
Food compatibility	See expanded material information

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

ambient temperature [°C]	-20 to 120
Nominal tightening torque [Nm]	20,0
Tolerance to nominal tightening torque	± 10 %
Product weight [g]	28,85
Pneumatic connection 1	Male thread G1/4
Pneumatic connection 2	For hose exterior diameter 8 mm
Stud material	High-alloyed stainless steels
Material information	RoHs compliant
Gasket material	PEEK
Housing material	High-alloyed stainless steels