

Elbow Click Fitting NPKA-L-G18-Q6-P10 - Festo 1655429

Item no. FES-1655429

Manufacturer Festo

EAN 4052568062262

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

TECHNICAL DATA

Baugröße BG	Standard
Betriebsdruck max [bar]	10.000000
Design	Push-pull principle
HS-Code	39174000
Material	PA66-GF30
Medium	Compressed air, water
Mounting position	arbitrary
Nennweite DN [mm]	4
Pneumatic connection	G1/8
Temperature (max.)	60
Weight	0.008 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

size	Standard
Nominal width [mm]	4
Seal type on stud	gasket
installation position	arbitrary
Packing size	10
Construction set up	Push-pull principle
Operating pressure [bar]	-0.95 to 10
Temperature depending operating pressure [bar]	-0.95 to 10
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-] Water according to manufacturer declaration at www.festo.com
Information about operating and control medium	Oiled operation possible

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com
esd.equipment

Page 1/2

Food compatibility	See expanded material information
ambient temperature [°C]	-10 to 60
Max. tightening torque [Nm]	2
Nominal tightening torque [Nm]	1,25
Tolerance to nominal tightening torque	± 20 %
Product weight [g]	7,5
Pneumatic connection 1	Male thread G1/8
Pneumatic connection 2	For hose exterior diameter 6 mm
Material information	RoHs compliant
Housing material	PA66-GF30
Thread sealing material	PA66-GF30 / TPE-U
Sleeve material	POM
Tube seal, hose seal material	NBR