

Semi-Rotary Drive DRVS-25-180-P - Festo 1845717

Item no. FES-1845717

Manufacturer Festo

EAN 4052568264222

Festo rotary actuator for defined swivel motion and positioning in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
HS-Code	84123900
Pneumatischer Anschluss	M5
Weight	0.49 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo rotary actuator for defined swivel motion and positioning in automation. The key technical data of this genuine Festo article are listed below.

size	25
Dampening angle [deg]	0,5
Swivel angle [deg]	0 to 180
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Construction set up	Rotary vane
Position detection	For proximity switch
Variants	Tap shaft
Operating pressure [bar]	2 to 8
Max. swivel frequency at 6 bar [Hz]	3
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	0 to 60
Max. axial force [N]	40
Max. radial force [N]	60
Theoretical torque at 6 bar [Nm]	5,00
Permitted mass moment of inertia [kg/m²]	0,01200
Product weight [g]	494
Fastening type	with female thread
Pneumatic connection	M5
Material information	RoHs compliant
Drive shaft material	Nickel-plated steel
Seals material	TPE-U(PU)
Housing material	Aluminium die casting painted