

Guide Unit EAGF-V2-KF-50-320 - Festo 2784164

Item no. FES-2784164


Manufacturer Festo

EAN 4052568266288

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

HS-Code	84821090
Hub [mm]	320.000000
Weight	6 kg
Werkstoff	Aluminium



DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

size	50
Stroke [mm]	320
Reversing play [µm]	0
installation position	arbitrary
Guide	ball guide
Construction set up	Guide
Corrosion resistant class KBK	0 - No corrosion stressing
ambient temperature [°C]	-20 to 80
Max. force Fy [N]	1.260
Max. force Fy static [N]	1.600
Max. force Fz [N]	1.260
Max. force Fz static [N]	1.600
Max. torque Mx [Nm]	65
Max. torque Mx static [Nm]	83

Max. torque My [Nm]	70
Max. torque My static [Nm]	89
Max. torque Mz [Nm]	70
Max. torque Mz static [Nm]	89
Pushing force [N]	15,0
Moving mass [g]	3.583
Product weight [g]	5.627
Centre of mass of the moved mass at 0 mm stroke [mm]	46
Supplement centre of mass of the moved mass per 10 mm stroke [mm]	4,3
Fastening type	with female thread
Material information	Copper and PTFE-free RoHs compliant
Guide element material	Quenched and tempered steel
Housing material	Aluminium wrought alloy anodized
Joch plate material	Steel