

Standards-Based Cyli DSBC-40-30-D3-PPSA-N3 - Festo 3660761

Item no. FES-3660761

Manufacturer Festo

EAN 4052568273323

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Ausführungstyp	einseitige Kolbenstange
Betriebsdruck max [bar]	12.000000
Bore (mm)	40.000000
Corrosion resistance class CRC	2 - moderate corrosion stress
Cushioning	PPS: Self-setting pneumatic end position dampening
Design	Piston, piston rod, profile tube
Funktion	double-acting
HS-Code	84123100
Hub [mm]	30
Medium	Compressed air
Mounting position	arbitrary
Norm	ISO 15552
Pneumatic connection	G1/4
Position sensing	Yes
Series	DSBC
Temperature (max.)	80
Weight	0.9 kg



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	30
Piston diameter	40 mm
Piston rod thread	M12x1,25
Dampening	PPS: Self-setting pneumatic end position dampening
installation position	arbitrary
Complies to standard	ISO 15552

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Piston rod end	Male thread
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	0.6 to 12
Principle of operation	double acting
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-20 to 80
Impact energy at the end positions [J]	0,7
Dampening length [mm]	19
Theoretical force at 6 bar, Return flow [N]	633
Theoretical force at 6 bar, flow [N]	754
Moving mass at 0 mm stroke [g]	205
Weight supplement per 10 mm stroke [g]	37
Base weight at 0 mm stroke [g]	740
Supplement moved mass per 10 mm stroke [g]	16
Fastening type	With female thread With Accessories Selectively:
Pneumatic connection	G1/4
Material information	RoHs compliant
Cover material	Alu-Druckguss, beschichtet
Werkstoff Kolbendichtung	TPE-U(PU)
Piston material	Aluminium wrought alloy
Piston rod material	High-alloyed steel
Werkstoff Kolbenstangen-Dichtabstreifer	TPE-U(PU)
Werkstoff Pufferdichtung	TPE-U(PU)
Werkstoff Pufferkolben	POM
Cylinder tube material	Aluminium-Knetlegierung, gleiteloziert
Nut material	Zinc plated steel
Bearing material	POM
Flush screw material	Zinc plated steel