

Hand Lever Valve VHER-P-H-B43U-M5 - Festo 3410683

Item no. FES-3410683


Manufacturer Festo

EAN 4052568269524

Festo pneumatic component for industrial automation and compressed-air applications in proven quality.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	M5
Weight	0.12 kg
Werkstoff	Polyamid (PA)



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic component for industrial automation and compressed-air applications in proven quality. The key technical data of this genuine Festo article are listed below.

Valve function	4/3 ventilated
Actuation type	Manually
Build.width [mm]	37
Normal nominal flow [l/min]	170
Operating pressure [bar]	0 to 10
Information about operating pressure	Vacuum mode -0.95 to 0 bar, may only be connected to connection 3 For two-pressure mode, the pressure on connection 1 must be higher than on connection 3.
Construction set up	Rotary disc
Nominal width [mm]	4
Exhaust function	Can be throttled
User information	Only actuate by hand

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Sealing principle	Hard
Control type	Direct
Flow direction	Not reversible
Freedom from cross-talk	yes
Switching position display	With Accessories
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	2 - moderate corrosion stress
Medium temperature [°C]	-20 to 80
ambient temperature [°C]	-20 to 80
Actuation torque [Nm]	0,5
Product weight [g]	95
Fastening type	Front panel integration With throughway bores Selectively:
Pneumatic connection 1	M5
Pneumatic connection 2	M5
Pneumatic connection 3	M5
Pneumatic connection 4	M5
Material information	Copper and PTFE-free RoHs compliant
Seals material	NBR
Housing material	PA
Lever material	PA
Actuation fuse	With Accessories lockable