

# Sub-Base VMPAL-AP-4X14-QS8-1 - Festo 561085

<b>Item no.</b>	FES-561085	<b>Manufacturer</b>	Festo
<b>Manufacturer no.</b>	VMPAL-AP-4X14-QS8-1	<b>EAN</b>	4052568260040

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections.

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Betriebsdruck max [bar]	<b>10.000000</b>
Condition of article	<b>New</b>
HS-Code	<b>84819000</b>
Weight	<b>0.131 kg</b>



## STANDARDS & COMPLIANCE

**ISO 8573-1:2010**

## DESCRIPTION

Festo fitting or line component for fast, leak-tight and pressure-resistant compressed-air connections. The key technical data of this genuine Festo article are listed below.

Width [mm]	59,6
Length [mm]	107,3
Pitch dimension [mm]	14,9
Valve size [mm]	14
Max. number of valve spaces	4
Flow direction	Reversible
Valve island structure	Valve sizes mixable
Operating pressure [bar]	-0.9 to 10
Control pressure [bar]	3 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	3 - severe corrosion stress

ambient temperature [°C]	-5 to 50
Product weight [g]	130,80
Pneumatic connection 2	For hose exterior diameter 8 mm
Pneumatic connection 4	For hose exterior diameter 8 mm
Material information	RoHs compliant
Connection plate material	PA reinforced
Max. number of valve coils	4