

Selector Valve VHEF-ES-B53C-G14 - Festo 4106819

Item no. FES-4106819 Manufacturer Festo EAN 4052568291341

Festo valve for fast, reliable control of compressed-air direction and flow.

TECHNICAL DATA

Betriebsdruck max [bar]	10.000000
HS-Code	84812090
Pneumatischer Anschluss	G1/4
Weight	0.28 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo valve for fast, reliable control of compressed-air direction and flow. The key technical data of this genuine Festo article are listed below.

Valve function	5/3 closed
Actuation type	Manually
Build.width [mm]	20
Normal nominal flow [l/min]	1.200
Betriebsdruck Mpa [MPa]	-0,095 bis 1
Operating pressure [bar]	-0.95 to 10
Construction set up	Piston pusher
Nominal width [mm]	7,0
Exhaust function	Can be throttled
User information	Only actuate by hand
Sealing principle	Soft
installation position	arbitrary

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Control type	Direct
Flow direction	Reversible
Überdeckung	positive Überdeckung
Max. switching frequency [Hz]	0,5
Operating medium	Compressed air to ISO 8573-1:2010 [7:-:-]
Information about operating and control medium	Oiled operation possible (required in further operations)
Corrosion resistant class KBK	1 - low corrosion stress
Medium temperature [°C]	-10 to 60
ambient temperature [°C]	-10 to 60
Actuation torque [Nm]	0,3
Max. force on actuation [N]	200
Max. cross-force on actuation [N]	200
Product weight [g]	268
Fastening type	Front panel integration With throughway bores Selectively:
Pneumatic connection 1	G1/4
Pneumatic connection 2	G1/4
Pneumatic connection 3	G1/4
Material information	RoHs compliant
Cover material	PA reinforced
Seals material	NBR
Housing material	Aluminium wrought alloy, anodised
Lever material	PA reinforced
Pneumatic connection 4	G1/4
Pneumatic connection 5	G1/4
Hand assist actuation	Ratcheting