

Compact Cylinder DPDM-32-5-S-PA - Festo 4828428

Item no. FES-4828428

Manufacturer Festo

EAN 4052568292102

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Bohrung (mm)	32.000000
HS-Code	84123100
Hub [mm]	5.000000
Pneumatischer Anschluss	G1/8
Weight	0.33 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	5
Piston diameter	32 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	Pressing single action
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	1.5 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)

Corrosion resistant class KBK	1 - low corrosion stress
ambient temperature [°C]	-10 to 80
Theoretical force at 6 bar [N]	445
Theoretical force at 6 bar, flow [N]	445
Moving mass at 0 mm stroke [g]	85,0
Weight supplement per 10 mm stroke [g]	51,0
Base weight at 0 mm stroke [g]	310,0
Supplement moved mass per 10 mm stroke [g]	9,0
Fastening type	With throughway bores With female thread Selectively:
Pneumatic connection	G1/8
Material information	RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	TPE-U(PU)
Housing material	Aluminium wrought alloy, anodised
Piston rod material	High-alloyed stainless steels