

Compact Cylinder DPDM-25-15-PA - Festo 4829572

Item no. FES-4829572

Manufacturer Festo

EAN 4052568292409

Festo pneumatic cylinder for precise linear motion and defined force in automation.

TECHNICAL DATA

Betriebsdruck max [bar]	8.000000
Bohrung (mm)	25.000000
HS-Code	84123100
Hub [mm]	15.000000
Pneumatischer Anschluss	M5
Weight	0.25 kg
Werkstoff	Aluminium



STANDARDS & COMPLIANCE

ISO 8573-1:2010

DESCRIPTION

Festo pneumatic cylinder for precise linear motion and defined force in automation. The key technical data of this genuine Festo article are listed below.

Stroke [mm]	15
Piston diameter	25 mm
Dampening	P: Elastic silencer rings / plates double-sided
installation position	arbitrary
Principle of operation	double acting
Construction set up	Piston piston rod profile tube
Position detection	For proximity switch
Variants	One-sided piston rod
Operating pressure [bar]	1 to 8
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Information about operating and control medium	Oiled operation possible (required in further operations)

Corrosion resistant class KBK	2 - moderate corrosion stress
ambient temperature [°C]	-10 to 80
Theoretical force at 6 bar [N]	295
Theoretical force at 6 bar, flow [N]	295
Moving mass at 0 mm stroke [g]	58,0
Weight supplement per 10 mm stroke [g]	33,5
Base weight at 0 mm stroke [g]	205,0
Supplement moved mass per 10 mm stroke [g]	6,5
Fastening type	With throughway bores With female thread Selectively:
Pneumatic connection	M5
Material information	RoHs compliant
Cover material	Aluminium wrought alloy
Seals material	TPE-U(PU)
Housing material	Aluminium wrought alloy, anodised
Piston rod material	High-alloyed stainless steels
Theoretical force at 6 bar, Return flow [N]	247