

# ERSADUR-LF Soldering Tip, Straight Chisel, 12 mm, for i-Tool HighPower - Erska 0242CDLF120

Item no. ER-0242CDLF120

Manufacturer Erska

EAN 4003008098709

Straight, chisel-shaped ERSADUR-LF permanent soldering tip with a 12 mm tip width for the HighPower-Tool (0240CDJ) soldering iron of the i-CON Vario HP station. Its galvanically iron-plated, chrome-protected surface ensures a long service life and excellent heat transfer. Ideal for demanding soldering work with high heat demand.

## TECHNICAL DATA

|                        |                  |
|------------------------|------------------|
| Ausführungsklasse      | TEC              |
| Country of Manufacture | Germany          |
| ESD equipment          | ESD Lötstationen |
| Weight                 | 0.1 kg           |



## DESCRIPTION

Permanent soldering tip, straight, chisel-shaped, 12 mm, with ERSADUR-LF coating. Suitable for the HighPower-Tool soldering iron (0240CDJ) of the i-CON Vario HP soldering station in version OICV2000HP.

ERSADUR soldering tips are produced to a high standard and built for continuous operation. In a special galvanic process they are plated with an iron layer and protected against corrosion and oxidation by an additional chromium layer. Perfect heat transfer protects the heating element of the soldering iron against overheating and premature wear. ERSKA offers a comprehensive range of soldering and desoldering tips for the ERSKA i-Tool, i-Tool Pico, i-Tool Nano (i-CON soldering stations) and HighPower-Tool.

## TECHNICAL DATA

| Feature              | Value                      |
|----------------------|----------------------------|
| Tip series           | 0242                       |
| Tip design           | straight                   |
| Tip shape            | chisel-shaped              |
| Tip diameter/width   | 12.00 mm                   |
| Tip coating          | Permanent tip (ERSADUR-LF) |
| Shaft outer diameter | 12.20 mm                   |

| Feature              | Value   |
|----------------------|---------|
| Shaft inner diameter | 7.00 mm |
| Total length         | 45 mm   |
| RoHS compliant       | No      |