

## ESD spray paint AstraStat type S, 2K PU, 400 ml, RAL 9005 black - Statech Systems EP1101007

Item no. EP1101007

Manufacturer Statech Systems

Permanently dissipative two-component polyurethane spray paint in black (RAL 9005), 400 ml aerosol can. Turns insulating and low-ohmic surfaces into a durable ESD-safe coating with a surface resistance below  $3.5 \times 10^7 \Omega$  per IEC 61340-5-1.

### TECHNICAL DATA

|                   |                    |
|-------------------|--------------------|
| Ausführungsklasse | ESD (antistatic)   |
| Colour            | Black              |
| ESD equipment     | ESD-Reiniger       |
| Norm              | IEC 61340-5-1      |
| Sales unit        | 1 Spraydose 400 ml |
| Weight            | 0.5 kg             |



### STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

### DESCRIPTION

AstraStat type S converts insulating or low-ohmic surfaces into a dissipative ESD-protected area. The two-component polyurethane paint cures into a chemical-resistant, permanently dissipative layer for shelves, tables and containers in the EPA.

### BENEFITS

- Permanently dissipative with surface resistance below  $3.5 \times 10^7 \Omega$  per IEC 61340-5-1
- Very good coverage and a chemical-resistant, hard-wearing surface
- Wide-spray nozzle for fine atomisation and even paint application

### TECHNICAL DATA

- Type: two-component polyurethane spray paint
- Colour: RAL 9005, black
- Content: 400 ml aerosol can
- Surface resistance: below  $3.5 \times 10^7 \Omega$
- Working time after activation: 5 hours

## **APPLICATIONS**

Suitable for coating storage shelves, trolleys, table surfaces, containers, workpiece carriers and drawer units. For plastics such as ABS, PA, PC, POM, PP/EPDM, PPO, PUR and PVC the 4S-HP-S adhesion primer is required.

## **STANDARDS AND COMPLIANCE**

- IEC 61340-5-1