

R KLT box 60 x 40 x 15 cm - Auer ESD R-KLT 6415

Item no. ESD R-KLT 6415

Manufacturer Auer

R KLT small load carrier to VDA dimensions in the medium weight class, with a ribbed base for a secure stand and material flow up to around 20 kg payload. Ribbed base with stacking lugs and groove for a secure stand when filled

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	Germany
HS-Code	39231000
Note	Stück auf Palette - 80
Weight	2.37 kg



STANDARDS & COMPLIANCE

IEC 61340-5-1

DESCRIPTION

R KLT small load carrier to VDA dimensions in the medium weight class, with a ribbed base for a secure stand and material flow up to around 20 kg payload.

- Ribbed base with stacking lugs and groove for a secure stand when filled
- Designed for payloads up to around 20 kg
- Safety rim height allows reliable stacking of several containers
- Reinforced impact surfaces at front and long side for the use of pulling technology
- Lifting slots ease the vertical attachment of gripping devices
- Dissipative design to IEC 61340-5-1, volume resistance $10^3 < 10^{10}$ Ohm/cm for safe handling of electrostatic discharge sensitive components.

Used in the automotive industry and industrial intralogistics for the standardised supply and transport of parts.

Made of polypropylene (PP) to VDA standard, manufactured in Germany.

Technical data

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Outer dimensions L x W x H	60 x 40 x 15 cm
Internal dimensions at base L x W x usable height	54.4 x 36.4 x 10.95 cm
Base design	Sturdy base ribbing, closed
Volume	22 liter
Material	ESD PP
Weight	2.37 kg
Colour	traffic black similar RAL 9017
Production information	Colour fluctuations are unavoidable due to raw material reasons
Special volume resistance	$10^3 < 10^{10}$ Ohm/cm