

ESD grounding box with 3 x 4 mm sockets, 1 MΩ each - A1-ESD EP0102004

Item no. EP0102004

Manufacturer A1-ESD

Grounding box with three 4 mm sockets at a 90-degree angle, each with a 1 MΩ protective resistor. The 3 m earthing lead ends in a screw eyelet for an M5 thread for fixed grounding.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Norm	IEC 61340-5-1
Sales unit	1 Stück
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The A1-ESD grounding box EP0102004 provides three 4 mm sockets at a central ground point and suits earthing cables with 4 mm plugs. Each connection has a 1 MΩ protective resistor; the 3 m earthing lead is connected to protective earth via a screw eyelet for an M5 thread.

BENEFITS

- Three 4 mm sockets for earthing cables with 4 mm plugs
- 1 MΩ protective resistor per connection to IEC 61340-5-1
- Mounted at a 90-degree angle for fitting at the bench edge
- 3 m earthing lead with a screw eyelet for an M5 thread

TECHNICAL DATA

- Connection: 3 x 4 mm socket
- Resistance: 1 MΩ protective resistor each
- Cable length: 3.00 m
- Grounding: screw eyelet for M5 thread
- Mounting: 90-degree angle

- Selling unit: 1 piece

APPLICATION

Central grounding of ESD workstations that use 4 mm plug systems only.

STANDARDS AND COMPLIANCE

Supports the IEC 61340-5-1 requirements for grounding within the EPA.