

ESD grounding connection set for floor coverings up to 10 x 20 m

Item no. EP0102007

Manufacturer A1-ESD

Complete grounding connection set for ESD floor coverings up to 10 m x 20 m. With a 4 mm test point for resistance measurement, copper grounding tape, cable and mounting hardware.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
Depth	10
Height	55
Sales unit	1 Set
Weight	0.1 kg
Width	45



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The grounding connection set links an ESD floor covering of up to 10 m x 20 m to ground in a controlled way. The wall-mounted connection box offers a 4 mm connection point for measuring the floor resistance with a high-resistance meter.

BENEFITS

- Grounds an area of up to 10 m x 20 m
- 4 mm test point for floor resistance measurement
- Complete kit with tape, cable and fixings

TECHNICAL DATA

- Connection box dimensions: 45 mm x 55 mm x 10 mm
- Mounting: wall mount
- Test point: 4 mm for high-resistance meter

SCOPE OF DELIVERY

- 2 m of self-adhesive copper grounding tape

- 3 m green-yellow cable with M5 ring terminal
- 2 screws
- 6 cable clips
- 1 spare M5 ring terminal

APPLICATION

Grounding of ESD floor coverings in EPA areas of electronics manufacturing.

STANDARDS

Suitable for building EPA areas to IEC 61340-5-1.